

## Palm Buttons • Ring Guards • Enclosures



### Features/Applications

Rees Palm Button Switches are designed and manufactured to meet demanding performance specifications. They have been the standard in the metal stamping and automotive industries for many years. Our ergonomically friendly “low force” palm buttons (04957-012) and unique emergency stop buttons (02182-002) have established themselves as the premier products when dependable starting and stopping is required.

Look to Rees for many of your accessory items such as; ring guards, mounting enclosures, and other heavy duty controls.

Various styles are listed below. For additional styles or contact configurations please refer to our online catalog or contact us directly.

00662-103	Palm Button Green Plunger	Slow-Make/Slow Break Momentary Contacts	NO + NC NEMA 12/13, IP 65	3.0 lbs. Operating Force
02182-002*	Palm Button Red Plunger	Positive Break Contacts Maintained	NO + NC NEMA 12/13, IP 65	Latches when depressed Operate latch to release
02718-000	Orange Four Hole Enclosure	Ideal for Run Bar Applications	External Mounting Feet	Other enclosure options are available
02765-100	Yellow Single Hole Enclosure	Ideal for Rees Standard Palm Buttons	External Mounting Feet	Also available in black
04933-093	1.50 inch Ring Guard	Ideal for Rees Standard Palm Buttons	Painted Yellow	Available in various sizes
04957-012	Palm Button Chrome Plunger	Snap Action Contacts Standard Mounting	(2) NO + (2) NC NEMA 12/13, IP 65	1.9 lbs. Operating Force
04917-712	Palm Button with Ring Guard	Snap Action Contacts Large Mounting Pattern	(2) NO + (2) NC NEMA 12/13, IP 65	2.0 lbs. Operating Force

\*Please note that using our 01004-045 spacer/adaptor to offset the E-Stop switch on our run bar will allow more space for insertion of a padlock.



02765-100



00662-103



04917-712